BELT CONVEYOR FBC-250 / - 350 / - 500 / - 700

N.P.T GROUP



FEATURES:

- Heavy duty steel construction in galvanized or lacquered finish.
- Highly flexible construction to meet a wide range of requirements (length, width, belt quality, and output) and adaptable to the specific product to be conveyed.
- Capable of horizontal or inclined installation to facilitate many different applications.
- Open or totally enclosed design to suit customer requirements.
- Optional top and bottom covers supplied in sections (fixed or hinged) offering maximum security during operation as well as protection against dust, rain, and intense sunshine; bottom covers available in closed plate or mesh design.
- Easy belt alignment at the inlet end ensuring trouble free operation at all times; conveyors longer than 40 m can optionally be supplied with automatic belt tensioning (pneumatic or weight loaded).
- Optional drive arrangement and placement to suit individual plant layouts.
- Very efficient cleaning unit (scrapers) to ensure peak performance; a combination of scrapers and rotating brushes is also available.
- Large selection of belt designs and qualities to give the best possible transportation of a vast range of products
- Low maintenance costs and one-year parts warranty.

DIMENSIONS:

Model	Input Capacity (Ton/hr)	Required power (kW)	Main shaft revolution (rpm)	With belt (mm)		de dimei WxH (m		Weight (kG)
FBC-250	2.0 - 3.0	0.75 - 1/50	50	250	8000	400	300	200
FAK-350	4.0 - 5.0	1.1 - 1/50	50	350	8000	500	300	300
FAK-500	6.0 - 8.0	1.5 – 1/50	50	500	8000	650	400	400
FAK-700	10 - 12	2.2 – 1/50	50	700	8000	850	400	600

NPT Group H.O: 161/28/21 Binh Tri Dong Street Binh Tan District, HCMC Vietnam.	Varesin B.O: Local 13 Corregimiento Pueblo Nuevo Urbanizacion Las Praderas Panama.	Distributors:
Tel: +848. 54072938 Cell: +84 918 183 497 Fax: + 848. 62601256 E-mail: engineering@npt-group.com	Tel/Fax: + 224-2575, 392-3575 Tel/Cell: + 6614-1826 Website: www.faricela.com E-mail: ventas@faricela.com	